



Flanges for push-in pipes

The Flange Range

Article number: 20353724

Assembly instruction

Ring-seal has to be pushed with tension over the push-in pipe.
Pipeline has to be protected against axial displacements on both ends of the push-in pipe connection!
Admissible pressure differential inside the pipe system approx. 50 mbar.

- 1) Mounting screws to be provided by the customer, length = 50 mm
- 2) Standard pipe with loose flange
- 3) Flange for push-in pipe
- 4) Ring-seal for push-in pipe with flange connection

Material: Stainless steel

diameter DN: 350.0 MM

Quantity: 1

83,10 €

Fr. Jacob Söhne GmbH & Co.kg
HRA 3524 - AG Bad Oeynhausen
Persönlich haftende Gesellschafterin
Jacob Rohrsysteme
Beteiligungs-GmbH

Jacob Rohrsysteme
Beteiligungs-GmbH
HRB 3923 - AG Bad Oeynhausen
Geschäftsführer:
Klaudine Gericke / Patrick Jacob

Sparkasse Minden-Lübbecke
IBAN: DE64 4905 0101 0049 0010 76
BIC: WELA DE D1 MIN

Deutsche Bank Minden
IBAN: DE58 4907 0028 0286 1003 00
BIC: DEUT DE 38 490

